

# Jackson

## Technical data sheet




Based on testing by	CIRS
Total composition	100% PES
Composition top layer	100% PES
Composition base layer	100% PES
Water repellent finish	Yes
Fabric Backcoating	Not applicable
Useful fabric width	140 +/- 2% cms
Roll length	40 m
Fabric thickness	0,8 mm
Fabric weight	410 g/m <sup>2</sup>
HS code	5514309000

### Important fabric characteristics

- Upholstery fabrics are sensitive to direct influx of ultraviolet light (sun- or halogen light) and may discolour over time.
- Intense and dark colours are more sensitive to discoloration caused by ultraviolet light.
- Intense and dark colours have a lower rub fastness grade.
- Wet fabrics have a lower rub fastness grade.
- Dye lot differences may occur.
- Pilling caused by clotting of upholstery fabric fibres with dust or other fibres may occur.
- It is recommended to maintain the humidity level of the room to guarantee the elasticity of the fibres and avoid build-up of static electricity.
- Light and plain fabrics are more sensitive to staining.
- Direct contact with chemical solvents (e.g. in glue sprays) can deteriorate fabric properties.
- In contact with sharp objects scissors, cutters, nails ...) surface damage or pulled loops are unavoidable.
- Do not expose upholstery fabric to direct heat sources.

### Fabric care instructions



# Jackson

## Technical data sheet



### Technical specifications

<u>Martindale</u>		EN ISO 12947-2:2016
65000 rubs		
<u>pilling according to Martindale method</u>		EN ISO 12945-2:2000
note 4-5	500 rubs	
note 4-5	1.000 rubs	
note 4-5	2.000 rubs	
note 4	5.000 rubs	
<u>seam slippage</u>		EN ISO 13936-2:2004
3 mm	warp	
2 mm	weft	
<u>tear strength</u>		EN ISO 13937-3:2000
170 Nabs	warp	
43 Nabs	weft	
<u>tensile strength</u>		EN ISO 13934-1:2013
2300 daN	warp	
560 daN	weft	
<u>light fastness</u>		EN ISO 105-B02:2014
note 3-4 dark colours		
note 4 light colours		
<u>rub fastness - wet</u>		EN ISO 105-X12:2002
note 3-4 dark colours		
note 4-5 light colours		
<u>rub fastness - dry</u>		EN ISO 105-X12: 2002
note 4 dark colours		
note 5 light colours		